ST. LAWRENCE HIGH SCHOOL
A JESUIT CHRISTIAN MINORITY INSTITUTION

ANSWER KEY– 48
TOPIC – VISUAL BASIC

SUBJECT: COMPUTER APPLICATION   **CLASS: XI**
F.M.: 15   **DATE: 21.11.2020**

➢ **Choose the correct option:**   **(1X15=15)**

1) For…Next is a type of _____ statement:
(a) Relational   (b) Logical   (c) Arithmetic   **(d) Control**

2) Using InputBox command text is displayed as the message in the dialog box due to the following:
(a) Title   **(b) Prompt**   (c) DefaultValue   (d) None of these

3) This part of InputBox command gives the title in the title bar of the dialog box:
(a) Title   (b) Prompt   (c) DefaultValue   (d) None of these

4) Do Until…Loop is a type of _____ statement:
(a)) Relational   **(b) Control**   (c) Arithmetic   (d) None of these

5) This command is used to accept text value in a dialog box:
(a) InputBox   (b) PutBox   (c) InBox   (d) None of these

6) _____ statements are used to control the flow of program execution:
(a) Handling   (b) Alter   **(c) Control**   (d) None of these

7) This is called the conditional statement because it is used to take decision depending upon specified condition:
(a) TextBox   (b) InputBox   (c) print   **(d) if..else**

8) This data type is used to store alphanumeric values:
(a) Thread   **(b) String**   (c) Character   (d) None of these

9) This command is used to convert the text into a number format so that the calculation can be performed:
(a) Mod   **(b) Val**   (c) Numerical   (d) None of these

10) This clause in the Dim statement allows defining the data type of the variable:
(a) As Storage   (b) As Data Type   (c) As Data   **(d) As Type**

11) This is a numeric data type to store integer values in the range of 0 to 255:
(a) Integer   (b) Single   (c) Long   **(d) Byte**

12) Do While is a type of _____ statement:
(a) Relational   (b) Logical   (c) Arithmetic   **(d) Control**

13) This part of InputBox command gives the default text that appears in the imput field, which the user may change:
(a) Title   (b) Prompt   **(c) DefaultValue**   (d) None of these

14) The variables are declared with this statement:
(a) int   **(b) Dim**   (c) store   (d) variable

15) The following is a type of arithmetic operator:
(a) +   (b) AND   (c) >=   (d) None of these

***

PRITHWISH DE

2